



# Q-SUN Xenon Test Chambers

## Overview

Q-SUN® xenon arc chambers reproduce the damage caused by full-spectrum sunlight and rain. In a few days or weeks, Q-SUN testers can reproduce the damage that occurs over months or years outdoors.

## Features

Q-SUN xenon arc chambers are available in three different models: the tabletop Xe-1, and full-sized Xe-2 and Xe-3. Each air-cooled tester features Q-Lab's renowned reliability and ease of maintenance. All testers have standard datalogging via ethernet, a variety of standard sample holders and a remarkably simple user interface available in five languages.

	Xe-1	Xe-2	Xe-3
Chamber Type	Flat Array	Rotating Rack	Flat Array
Specimen Capacity	17	31	55
Specimen Orientation (measured from horizontal)	10°	90°	10°
Full Spectrum, Ozone-Free Xenon Arc Lamps - 1800 W	1	1	3
Optional Water Spray	●	●	●
SOLAR EYE® Irradiance Control (340 nm, 420 nm or TUV)	●	●	●
Relative Humidity Control	—	●	●

## Optical Filters and Radiometers

Q-SUN optical filters are very durable and all but IR filters maintain the required spectrum indefinitely, lasting for years under normal use. The application or test standard dictates which filter to use. Xe-1 and Xe-3 filters are flat, while the Xe-2 filter lantern consists of an outer borosilicate or quartz cylinder and 14 inner filters.

	Xe-1	Xe-2	Xe-3	Irradiance (W/m²)			Radiometer (CR20/xxx)		
				@340 nm	@420 nm	@TUV	340 nm	420 nm	TUV
Daylight - Q	●	●	●	0.25 - 0.68	0.45 - 1.50	20 - 75	D	420	TUV
Daylight - B/B	●	●	●	0.25 - 0.68			BBF		
Daylight - F	●	●	●	0.25 - 0.80			BBF		
Extended UV - Quartz	●	—	●	0.25 - 0.68			QZ		
Extended UV - Q/B	●	●	●	0.25 - 0.68			QB		
Window - Q	●	●	●	0.25 - 0.55		20 - 70	W		
Window - B/SL	●	●	●	0.25 - 0.55			BSL		
Window - SF5	●	—	●	—			—		
Window - IR	●	●	●	—		20 - 42	—		TUV/IR
Window - B04	—	●	—	—			—		

## Calibration, Temperature and Humidity Control

Q-SUN Xe-2 and Xe-3 testers simultaneously control chamber air and black panel (uninsulated/BP) or black standard (insulated/IBP/BST) temperature; the Xe-1 controls either, but not both. An electronic humidity sensor provides precise control of relative humidity of the Xe-2 and Xe-3. All Q-SUN testers feature Q-Lab's patented AUTOCAL® system allowing quick and easy calibration. All calibrations are NIST traceable for ISO compliance.

	Xe-1	Xe-2	Xe-3
AUTOCAL CR20 Irradiance Control	●	●	●
CT202 Black Panel Thermometer	●	●	●
Chamber Air Temp Sensor	○	●	●
RH Sensor	—	●	●

○ Optional    ● Disposable



## Operating Specifications



Models <sup>1</sup>	Xe-1-B Xe-1-S		Xe-1-BC Xe-1-SC		Xe-2-H Xe-2-HS		Xe-3-H Xe-3-HS	Xe-3-HDS <sup>2</sup> Xe-3-HBS	Xe-3-HC Xe-3-HSC	
<b>Black Panel Temp<sup>3</sup> (°C)</b>	<b>BP</b>	<b>IBP/BST</b>	<b>BP</b>	<b>IBP/BST</b>	<b>BP</b>	<b>IBP/BST</b>	<b>BP</b>	<b>IBP/BST</b>	<b>BP</b>	<b>IBP/BST</b>
Light Cycle	45 - 90	50 - 100	25 - 90	25 - 100	50 - 100	55 - 105	45 - 110	50 - 120	35 - 110	36 - 120
Light Cycle w/IR Filter	40 - 70	45 - 80	20 - 70	20 - 80	35 - 85	40 - 90	40 - 90	45 - 100	30 - 90	31 - 100
Dark Cycle	25 - 50	25 - 50	10 - 50	10 - 50	25 - 45	25 - 45	25 - 50	25 - 50	15 - 50	16 - 50
<b>Chamber Air Temp<sup>3</sup> (°C)</b>	N/A		15 - 50 15 - 50 10 - 40		35 - 65 35 - 65 25 - 45		35 - 65 35 - 65 25 - 50		25 - 65 25 - 65 16 - 50	
Light Cycle										
Light Cycle w/IR Filter										
Dark Cycle										
<b>Relative Humidity<sup>3</sup></b>	N/A				95% - 20%					
<b>Specimen Area</b>	9.88" d x 18.00" w (25 x 46 cm)		9.88" d x 18.00" w (25 x 46 cm)		11.9" h x 9.8" ø (30 x 25 cm)		17.75" d x 28.25" w (45 x 72 cm)		17.75" d x 28.25" w (45 x 72 cm)	
<b>Specimen Capacity and Size</b>	15 specimens @ 2" x 4" (51 x 102 mm)		15 specimens @ 2" x 4" (51 x 102 mm)		31 specimens @ 1.8" x 4.8" (46 x 122 mm)		51 specimens @ 2" x 4" (51 x 102 mm)		51 specimens @ 2" x 4" (51 x 102 mm)	
<b>Inlet Water Pressure</b>	H Models: 10-90 psi (69-620 kPa); S Models: 30-90 psi (207-620 kPa)									
<b>Inlet Water Purity</b>	H Models: <20 ppm total dissolved solids; S Models: <1 ppm total dissolved solids and <0.1 ppm silica									
<b>Water Consumption</b>	0.1 L/min (spray)		0.1 L/min (spray)		0.5 L/min (spray) 24 L/day (humidifier)		0.1 L/min (spray) 0.4 L/min (front & back spray) 44 L/day (humidifier)		0.1 L/min (spray) 44 L/day (humidifier)	
<b>External Dimensions<sup>4</sup> (w x h x d)</b>	30.5" x 20.5" x 25.5" (78 x 52 x 65 cm)		30.5" x 54.5" x 31" (78 x 138 x 79 cm) <i>Xe-1 &amp; Chiller</i>		36" x 65.5" x 27" (91 x 166 x 69 cm)		36" x 72" x 39" (91 x 183 x 99 cm)		30.5" x 37" x 37" (78 x 94 x 94 cm) <i>Chiller Only</i>	
<b>Weight (actual)</b>	110 lbs (50 kg)		272 lbs (124 kg)		379 lbs (172 kg)		420-512 lbs (190-233 kg)		186 lbs (85 kg) <i>Chiller Only</i>	
<b>Weight (shipping<sup>5</sup>)</b>	230-320 lbs (105-145 kg)		454-545 lbs (205 -248 kg)		520 lbs (236 kg)		675-750 lbs (305-340 kg)		227 lbs (104 kg) <i>Chiller Only</i>	
<b>Electrical Requirements</b>	208V ± 10% 1-Φ, 50/60 Hz, 12A ----- 230V ± 10% 1-Φ, 50/60 Hz, 11A		208V ± 10% 1-Φ, 50/60 Hz, 19A; ----- 230V ± 10% 1-Φ, 50/60 Hz, 16A		208V ± 10% 1-Φ, 50/60 Hz, 24A ----- 230V ± 10% 1-Φ, 50/60 Hz, 23A		208/230V ± 10% 3-Φ, 50/60 Hz, 39A ----- 400V ± 10% 3-Φ, 50/60 Hz, 26A		208/230V ± 10% 3-Φ, 50/60 Hz, 44A; or ----- 400V ± 10% 3-Φ, 50/60 Hz, 26A	

1 Nomenclature Designations: basic (B), spray (S), humidity (H), dual spray (D), chiller (C), back spray (BS)

2 Model Xe-3-HDS has a separate water reservoir that requires additional floor space (not shown in picture).

3 Min and max black panel (BP), insulated black panel (IBP/BST) and chamber air temperatures and relative humidity capabilities are dependent on ambient lab conditions. Interdependencies between these parameters limit achievable operating conditions in the tester.

4 Vent duct on back of Xe-3 is easily removed to reduce the depth from 39" (99 cm) to 34.5" (88 cm) to fit through small doors.

5 Actual shipping weights will vary depending upon model and whether the shipment is domestic, ocean or air.

## Warranty

The Q-SUN Xenon Test Chamber is guaranteed against defects in workmanship or materials for one year. Liability is limited to replacing or repairing any part or parts which are defective in materials or workmanship and are returned to our factory, shipping costs prepaid. Liability in all events is limited to the purchase price paid. Damage due to accident or abuse is not covered. Labor cost is not covered. Q-Lab Corporation makes no other warranties, including implied warranties of merchantability or fitness for a particular purpose, except as may be expressly provided by Q-Lab Corporation in writing. Q-Lab Corporation shall not be liable for any incidental, consequential, special, or contingent damages arising out of the sale or use of any product.

## Q-Lab Corporation

[www.q-lab.com](http://www.q-lab.com)



**Q-Lab Headquarters**  
Westlake, OH USA  
Tel: +1-440-835-8700  
info@q-lab.com

**Q-Lab Florida**  
Homestead, FL USA  
Tel: +1-305-245-5600  
q-lab@q-lab.com

**Q-Lab Europe, Ltd.**  
Bolton, England  
Tel: +44-1204-861616  
info.eu@q-lab.com

**Q-Lab Arizona**  
Buckeye, AZ USA  
Tel: +1-623-386-5140  
q-lab@q-lab.com

**Q-Lab Deutschland GmbH**  
Saarbrücken, Germany  
Tel: +49-681-857470  
vertrieb@q-lab.com

**Q-Lab China 中国代表处**  
Shanghai, China 中国上海  
电话: +86-21-5879-7970  
info.cn@q-lab.com

LX-5046 © 2012 Q-Lab Corporation. All Rights Reserved.

Q-Lab, the Q-Lab logo, SOLAR EYE, AUTOCAL and Q-SUN are registered trademarks of Q-Lab Corporation.